





三山钎具 SANSHAN Rock Drilling Tools

整体钎 Integral drill steels

| 19mm | 长度 Length | | 钎头直径 Bit dia. | 重量 Weight approx kg | 三山型号 SANSHAN P/N | |
|---|---|----------------------|------------------|---------------------------|---------------------------|-----------------------|
| | 毫米 mm | 英尺 foot | | | | |
| 一字钎头整体钎 Chisel bit integral 钎柄 19mm×108mm Shank 19mm×108mm  | 400 | 1' 4" | 29 | 1.3 | 5H19-291508-0400-40-2 | |
| | 500 | 1' 8" | 29 | 1.5 | 5H19-291508-0500-40-2 | |
| | 800 | 2' 7" | 28 | 2.2 | 5H19-281508-0800-40-2 | |
| | 1000 | 3' 33/8" | 28 | 2.6 | 5H19-281508-1000-40-2 | |
| | 1200 | 3' 11" | 27 | 3.0 | 5H19-271508-1200-40-2 | |
| | 1600 | 5' 3" | 27 | 3.9 | 5H19-271508-1600-40-2 | |
| | 2400 | 7' 10" | 26 | 5.7 | 5H19-261508-2400-40-2 | |
| | 3200 | 10' 6" | 25 | 7.5 | 5H19-251508-3200-40-2 | |
| | 4000 | 13' 1" | 24 | 9.2 | 5H19-251508-4000-40-2 | |
| | 400 | 1' 4" | 24 | 1.3 | 5H19-241508-0400-40-2 | |
| | 800 | 2' 7" | 23 | 2.2 | 5H19-231508-0800-40-2 | |
| | 600 | 2' | 27 | 1.7 | 5H19-271508-0600-40-2 | |
| | 1200 | 3' 11" | 26 | 3.0 | 5H19-261508-1200-40-2 | |
| | 2000 | 6' 7" | 24 | 4.8 | 5H19-241508-2000-40-2 | |
| | 2400 | 7' 10" | 24 | 5.7 | 5H19-241508-2400-40-2 | |
| | 2700 | 8' 10" | 24 | 6.3 | 5H19-241508-2700-40-2 | |
| | 400 | 1' 4" | 35 | 1.3 | 5H19-351810-0400-40-2 | |
| | 800 | 2' 7" | 34 | 2.2 | 5H19-341810-0800-40-2 | |
| | 一字钎头整体钎 Chisel bit integral 钎柄 22mm×108mm Shank 22mm×108mm  | 400 | 1' 4" | 24 | 1.5 | 5H19-241508-0400-40-2 |
| | | 400 | 1' 4" | 29 | 1.5 | 5H19-291508-0400-40-2 |
| 600 | | 2' | 27 | 1.7 | 5H19-271508-0600-40-2 | |
| 800 | | 2' 7" | 23 | 2.3 | 5H19-231508-0800-40-2 | |
| 800 | | 2' 7" | 28 | 2.3 | 5H19-281508-0800-40-2 | |
| 1200 | | 3' 11" | 23 | 3.2 | 5H19-231508-1200-40-2 | |
| 1600 | | 5' 3" | 27 | 4.0 | 5H19-271508-1600-40-2 | |
| 2000 | | 6' 7" | 28 | 5.0 | 5H19-281508-2000-40-2 | |
| 2400 | | 7' 10" | 26 | 5.8 | 5H19-261508-2400-40-2 | |
| 3200 | | 10' 6" | 25 | 7.5 | 5H19-251508-3200-40-2 | |
| 采石整体钎 Plug hole integral steels 钎柄 19mm×108mm Shank 19mm×108mm  | | 长度 Length (mm) | 钎头直径 Bit dia. | 圆体长度 Turned length | 重量 Weight approx kg | 三山型号 SANSHAN P/N |
| | | 210 | 17 | 150 | 0.7 | 5H19-171308-0210-40-2 |
| | | 210 | 20 | 150 | 0.7 | 5H19-201308-0210-40-2 |
| | | 210 | 22 | 150 | 0.7 | 5H19-221308-0210-40-2 |
| | | 260 | 20 | 200 | 0.8 | 5H19-201308-0260-40-2 |
| | | 260 | 22 | 200 | 0.8 | 5H19-221308-0260-40-2 |
| | | 310 | 22 | 250 | 0.9 | 5H19-221308-0310-40-2 |
| | | 340 | 20 | 280 | 1.0 | 5H19-201308-0340-40-2 |
| | 钎柄 19mm×82mm Shank 19mm×82mm | 210 | 20 | 150 | 0.7 | 5H19-201308-0210-40-2 |
| | | 210 | 22 | 150 | 0.7 | 5H19-221308-0210-40-2 |

三山钎具 SANSHAN Rock Drilling Tools

整体钎 Integral drill steels

| 22mm | 长度 Length | | 钎头直径 Bit dia. | 重量 Weight approx kg | 三山型号 SANSHAN P/N |
|--|--------------|------------|------------------|---------------------------|-----------------------|
| | 毫米 mm | 英尺 Foot | | | |
| 一字钎头整体钎 Chisel bit integral 钎柄 22mm×108mm Shank 22mm×108mm  | 800 | 2' 7" | 34 | 3.0 | 5H22-341810-0800-40-2 |
| | 1600 | 5' 3" | 33 | 5.2 | 5H22-331810-1600-40-2 |
| | 2400 | 7' 10" | 32 | 8.0 | 5H22-321808-2400-40-2 |
| | 3200 | 10' 6" | 31 | 10.2 | 5H22-311808-3200-40-2 |
| | 4000 | 13' 1" | 30 | 12.9 | 5H22-301808-4000-40-2 |
| | 4800 | 15' 9" | 29 | 15.1 | 5H22-291508-4800-40-2 |
| | 5600 | 18' 4" | 28 | 17.6 | 5H22-281508-5600-40-2 |
| | 6400 | 21' | 27 | 20.1 | 5H22-271508-6400-40-2 |
| | 7200 | 23' 6" | 26 | 22.5 | 5H22-261508-7200-40-2 |
| | 800 | 2' 7" | 40 | 3.0 | 5H22-401810-0800-40-2 |
| | 1600 | 5' 3" | 39 | 5.2 | 5H22-391810-1600-40-2 |
| | 2400 | 7' 10" | 38 | 8.0 | 5H22-381810-2400-40-2 |
| | 3200 | 10' 6" | 37 | 10.2 | 5H22-371810-3200-40-2 |
| | 4000 | 13' 1" | 36 | 12.9 | 5H22-361810-4000-40-2 |
| | 4800 | 15' 9" | 35 | 15.1 | 5H22-351810-4800-40-2 |
| | 5600 | 18' 4" | 34 | 17.6 | 5H22-341810-5600-40-2 |
| | 6400 | 21' | 33 | 20.1 | 5H22-331810-6400-40-2 |
| | 7200 | 23' 6" | 32 | 22.5 | 5H22-321808-7200-40-2 |
| | 8000 | 26' 2" | 31 | 25.0 | 5H22-311808-8000-40-2 |
| | 400 | 1' 4" | 34 | 1.7 | 5H22-341810-0400-40-2 |
| | 800 | 2' 7" | 33 | 3.0 | 5H22-331810-0800-40-2 |
| | 1200 | 3' 11" | 32 | 4.1 | 5H22-321808-1200-40-2 |
| | 1600 | 5' 3" | 31 | 5.2 | 5H22-311808-1600-40-2 |
| | 2000 | 6' 7" | 30 | 6.7 | 5H22-301808-2000-40-2 |
| | 600 | 2' | 41 | 2.4 | 5H22-411810-0600-40-2 |
| | 1200 | 3' 11" | 40 | 4.3 | 5H22-401810-1200-40-2 |
| | 1800 | 5' 11" | 39 | 6.2 | 5H22-391810-1800-40-2 |
| | 2400 | 7' 10" | 38 | 8.0 | 5H22-381810-2400-40-2 |
| | 400 | 1' 4" | 41 | 1.7 | 5H22-411810-0400-40-2 |
| | 800 | 2' 7" | 29 | 3.0 | 5H22-291508-0800-40-2 |
| | 800 | 2' 7" | 38 | 3.1 | 5H22-381810-0800-40-2 |
| | 1200 | 3' 11" | 39 | 4.3 | 5H22-391810-1200-40-2 |
| | 1600 | 5' 3" | 36 | 5.2 | 5H22-361810-1600-40-2 |
| | 1800 | 5' 11" | 36 | 6.0 | 5H22-361810-1800-40-2 |
| | 2000 | 6' 7" | 32 | 6.7 | 5H22-321808-2000-40-2 |
| | 2400 | 7' 10" | 27 | 8.0 | 5H22-271508-2400-40-2 |
| | 3200 | 10' 6" | 27 | 10.2 | 5H22-271508-3200-40-2 |
| | 3200 | 10' 6" | 32 | 10.3 | 5H22-321808-3200-40-2 |
| | 6400 | 21' | 30 | 20.1 | 5H22-301808-6400-40-2 |
| | 8000 | 26' 2" | 26 | 25.0 | 5H22-261508-8000-40-2 |